

BOTTLE FILLER

BF38 Series MODEL A0000000-BF38

SEMI-RECESSED PUSHBUTTON OPERATED BOTTLE FILLER

STANDARD FEATURES

- 100 mesh inlet strainer
- Laminar Flow Water Supply
- 1 G.P.M. Fill Rate
- Lead Free
- Hinged Door
- Key Latch
- Meets ADA Forward and Side Reach Requirements
- Ligature-Resistant Design
- Vandal-Resistant Design

SUGGESTED SPECIFICATIONS

Model BF38 is Semi-Recessed pushbutton operated electric bottle filler that shall deliver a minimum of 8.0 GPH (30.3 LPH) of water at 50°F (10°C) cooled from 80°F (26.7°C) inlet water and 90°F (32.2°C). Bottle Filler can be mounted in a 4" or larger wall space for simple installation virtually anywhere. Housing has a slim and trim look that blends into your environment. Unit also has a strong, ligature resistant, and vandal-resistant design for years of trouble-free service. When installed properly, the bottle filler complies with ADA forward and side reach requirements. Unit includes an ADA compliant pushbutton requires less than 5 pounds push to activate valve. Bottle filler is fabricated of type 304 stainless steel polished to a satin finish.Unit is certified to ANSI A117.1, Public Law 111-380 (NO-LEAD), CHSC 116875 and NSF/ANSI 61, Section 9.



"INDOOR USE ONLY"

OPTIONS

(additional costs may be incurred)

🔲 -BF38

18 Gage 304 Stainless Steel

OPTIONS

Complies with the following

standards

(additional costs may be incurred)

🗋 -CG1	Custom Graphics
--------	-----------------

- -EG Enviro-Glaze
- Specify Color:
- -WF1 1500 gallon capacity, NSF 42+53, 1 micron lead reduction water filter

NSE/ANSI 61

GREEN

UPC

C

Test rating conditions are

compliant with ARI 1010.





MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com

Member of MORRIS GROUP

us

deral blic Law 1-380 o Lead) CE





BOTTLE FILLER

All dimensions are subject to manufactures tolerance of plus or minus ½" nominal and subject to change without notice. Murdock Mfg. assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock Mfg.™, Member of Morris Group International™. Please visit www.Murdockmfg.com for most current specifications.



Murdock Mfg.TM warrants that its products are free from defects in material or workmanship under normal use and service for a period of one year from date of shipment. Murdock's liability under this warranty shall be discharged solely by replacement or repair of defective material, provided MurdockTM is notified in writing within one year from date of shipment, F.O.B. Industry, California.

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING	Model Number & Options	Quantity	All dimensions are subject to manufactures tolerance of plus or minus ½" nominal and subject to		
	Company		change without notice. Murdock assumes no responsibility for use of void or superseded data. Dimensions		
CTIO PPR	Contact	Title	may change with the addition of optional accessories. Murdock Mfg. ™, Member of Morris Group		
SELE & A MA	Signature (Approval for Manufacturing)		International [™] . Please visit www.murdockmfg.com for most current specifications.		
	AUDDOCK MEC - 15125 Dreater Avenue - City of Industry CA 01746 USA				

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com