



HYDRANTS

Post Hydrant

MODEL M-275-RV

3/4" FREEZE RESISTANT, SELF-CLOSING
STOCK CAR HYDRANT

STANDARD FEATURES

Model M-275-RV delivers year-round service outside or in unheated buildings. To provide freeze resistant functionality, the control valve is located below the frost line. Pulling down on the lever raises the internal supply-line assembly to the open position, and the self-closing spring lowers the internal supply-line assembly to the closed position. Constructed of heavy lead-free brass, premium-quality gray iron and steel, the M-275-RV is designed for trouble-free reliability and easy maintenance, and is the hydrant of choice for RV washdown areas and elevated railroad platforms.

SUGGESTED SPECIFICATIONS

Hydrant shall be Murdock-Super Secur mode M-275-RV. Unit shall be capable of year-round use in freezing weather.

Unit shall extend below grade level so that centerline of supply inlet is positioned at or below frost line. Inlet shall have 3/4" NPT male connection.

Water shall be gravity-evacuated from inner supply column when valve is shut off.

Valve shall be lever operated. Lever shall be fabricated of one-piece iron casting finished with a heavy grade of oil-based green enamel. Stock, top, and base shall be fabricated of heavy, one-piece iron castings finished with a heavy grade of oil-based green enamel.

Inner supply assembly shall incorporate solid-brass castings. All solid brass castings shall conform to ASTM standards B61 and B62. Lead-free castings are used in all waterways.

Outer casing shall be black iron pipe, finished with a heavy grade of oil-based green enamel.

Hydrant shall consist of internal supply line and a surrounding outer casing pipe for protection of waterway.

Nozzle shall be solid brass casting, threaded for 3/4" NPS hose connection.

Self-coiling hose is provided with the hydrant.



☐ **Standard Model:** M-275-RV

DEPTH OF BURY (additional costs may be incurred)

- | | |
|---|---|
| ☐ 2 ft. (61 cm) | ☐ 5 ft. (152.4 cm) |
| ☐ 3 ft. (91.4 cm) | ☐ 6 ft. (182.9 cm) |
| ☐ 4 ft. (121.9 cm) | ☐ Other _____ |

OPTIONS (additional costs may be incurred)

- | | |
|-------------------------------|---|
| ☐ -BFH | Double ball check valve and vacuum breaker* |
| ☐ -VB | Vacuum breaker |
| ☐ -R01 | Shut off valve with plate* |
| ☐ | Plain end spout |
| ☐ | Sewer drain connection |

* See separate option sheets

Please visit www.murdock-supersecur.com
for most current specifications.



Member of
U.S. Green
Building
Council



Recyclable
Product

MURDOCK-SUPER SECUR A Member of Acorn Engineering's Family of Companies
15125 Proctor Avenue • City of Industry, CA 91746 USA • Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860

M-275-RV

New 02/08/11




HYDRANTS

Post Hydrant

MODEL M-275-RV

**3/4" FREEZE RESISTANT, SELF-CLOSING
STOCK CAR HYDRANT**



- | | | | |
|-------------------|--------------------|----------------------|----------------------------------|
| ① Lever | ⑤ 3/4" Hose thread | ⑧ Inner supply pipe | ⑫ Base |
| ② Top | ⑥ 25' Coiled hose | ⑨ Outer casting | ⑬ Valve |
| ③ Stirrup and tee | ⑦ Stock | ⑩ 41" Long chain | ⑭ 3/4" male NPT brass connection |
| ④ Slide | | ⑪ Chain holder clamp | |

ONE YEAR LIMITED WARRANTY - Parts are warranted for one (1) year from date of shipment.

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING

All dimensions are nominal and subject to manufacturer's change without notice.
Murdock-Super Secur assumes no responsibility for use of void or suspended data.
© Copyright 2009, Murdock-Super Secur, a division of Acorn Engineering Company.
Please visit www.murdock-supersecur.com for most current specifications.

Model Numbers & Options _____ Quantity _____
Company _____ Date _____
Contact _____ Title _____
Approval for Manufacturing/Signature _____

MURDOCK-SUPER SECUR A Member of Acorn Engineering's Family of Companies
15125 Proctor Avenue • City of Industry, CA 91746 USA • Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860

M-275-RV

New 02/08/11