



HYDRANTS

Post Hydrant

MODEL M-E123

3/4" FREEZE RESISTANT,
ECONO POST HYDRANT
WITH LEVER HANDLE

STANDARD FEATURES

Model M-E123 delivers year-round service outside or in unheated buildings. To provide freeze resistant functionality, the control valve is located below the frost line. Turning the lever handle raises or lowers the internal supply-line assembly, controlling the valve. Constructed of heavy lead-free brass, premium-quality gray iron and steel, the M-E123 is designed for trouble-free reliability and easy maintenance.



SUGGESTED SPECIFICATIONS

Hydrant shall be Murdock-Super Secur model M-E123. Unit shall be capable of year-round use in freezing weather.

Unit shall extend below grade level so that centerline of supply inlet is positioned at or below frost line. Inlet shall have 3/4" NPT female connection.

Water shall be gravity-evacuated from inner supply column when valve is shut off.

Valve shall be lever handle operated. Handle shall be fabricated of one-piece iron casting finished with a heavy grade of oil-based green enamel. Stock, top, and base shall be fabricated of heavy, one-piece iron castings finished with a heavy grade of oil-based green enamel.

Inner supply assembly shall incorporate solid-brass castings. All solid brass castings shall conform to ASTM standards B61 and B62. Lead-free castings are used in all waterways.

Outer casing shall be black iron pipe, finished with a heavy grade of oil-based green enamel.

Hydrant shall consist of internal supply line and a surrounding outer casing pipe for protection of waterway.

Nozzle shall be solid brass casting, threaded for 3/4" NPS hose connection.

Standard Model: M-E123

DEPTH OF BURY (additional costs may be incurred)

<input type="checkbox"/> 2 ft. (61 cm)	<input type="checkbox"/> 5 ft. (152.4 cm)
<input type="checkbox"/> 3 ft. (91.4 cm)	<input type="checkbox"/> 6 ft. (182.9 cm)
<input type="checkbox"/> 4 ft. (121.9 cm)	<input type="checkbox"/> Other _____

OPTIONS (additional costs may be incurred)

<input type="checkbox"/> - BFH	Double ball check valve and vacuum breaker*
<input type="checkbox"/> - VB	Vacuum breaker
<input type="checkbox"/> - LC1	Locking cover, less padlock*
<input type="checkbox"/> - R01	Shut off valve with plate*
<input type="checkbox"/>	Plain end spout
<input type="checkbox"/>	Sewer drain connection

* See separate option sheets

Please visit www.murdock-supersecur.com
for most current specifications.



Member of
U.S. Green
Building
Council



Recyclable
Product

MURDOCK-SUPER SECUR A Member of Acorn Engineering's Family of Companies
15125 Proctor Avenue • City of Industry, CA 91746 USA • Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860




HYDRANTS

Post Hydrant

MODEL M-E123

3/4" FREEZE RESISTANT, ECONO POST HYDRANT
WITH LEVER HANDLE



ONE YEAR LIMITED WARRANTY - Parts are warranted for one (1) year from date of shipment.

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING

All dimensions are nominal and subject to manufacturer's change without notice.
Murdock-Super Secur assumes no responsibility for use of void or suspended data.
© Copyright 2009, Murdock-Super Secur,
a division of Acorn Engineering Company.
Please visit www.murdock-supersecur.com
for most current specifications.

Model Numbers & Options _____ Quantity _____
Company _____ Date _____
Contact _____ Title _____
Approval for Manufacturing/Signature _____

MURDOCK-SUPER SECUR A Member of Acorn Engineering's Family of Companies
15125 Proctor Avenue • City of Industry, CA 91746 USA • Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860