

CONTEMPORARY DRINKING FOUNTAINS

GU Series MODEL GUF99-FRU1 FREEZE RESISTANT, PEDESTAL

MOUNTED DRINKING FOUNTAIN

STANDARD FEATURES

- Resistant to sunlight, heat, moisture and wear
- 18 gage, 304 stainless steel bowl
- Reinforced concrete with aggregate finish
- Polished stainless steel, anti-rotation non-squirt bubbler
- 100 mesh inlet strainer
- Freeze resistant valve system



MODEL: (Must Specify)

GUF98-FRU1 Tan Concrete Aggregate

GUF99-FRU1 Brown Concrete Aggregate (Shown)

OPTIONS

(additional costs may be incurred)				
☐ -CH30 ☐ -FS	Child height, 30" bubbler height Foot spray [If added, model requires -FRU2]			
🔲 -IGM	In-ground 14" mounting			
🔲 -JFFR1	Jug filler, recessed, freeze resistant, plain end with self-closing valve			
🗋 -PF	Pet fountain receptor [If added, model requires -FRU2]			
🗋 -RCS	Round concrete step for pedestal fountain			

SUGGESTED SPECIFICATIONS

Model GUF99-FRU1 is a pedestal mounted, vandal resistant and freeze resistant round drinking fountain made from an 18 gage, 304 stainless steel bowl mounted into a reinforced brown concrete aggregate pedestal. Unit shall be activated by a front mounted push button, by using less than 5 pounds of force, which pneumatically activates a water valve mounted below the frost line. An internally mounted adjustable stream regulator shall control the water flow. Bubbler shall be polished stainless steel with a non-squirt feature and operate on water pressure range of 20-105 psig. Unit shall adhere to NSF/ANSI 61, Section 9, Public Law 111-380(NO-LEAD), and CHSC 116875.



Please visit **www.murdockmfg.com** for most current specifications.







MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com Member of MORRIS GROUP



CONTEMPORARY DRINKING FOUNTAINS

All dimensions are subject to manufactures tolerance of plus or minus ½" nominal and subject to change without notice. Murdock Mfg. assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock Mfg.™, Member of Morris Group International™. Please visit www.Murdockmfg.com for most current specifications.



Murdock Mfg. \square warrants that its products are free from defects in material or workmanship under normal use and service for a period of one year from date of shipment. Murdock's liability under this warranty shall be discharged solely by replacement or repair of defective material, provided Murdock \square is notified in writing within one year from date of shipment, F.O.B. Industry, California.

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING	Model Number & Options	Quantity	All dimensions are subject to manufactures tolerance of plus or minus ½" nominal and subject to change without notice. Murdock assumes no responsibility for use of
ECTION S APPROV ANUFACT	Contact	Title	void or superseded data. Dimensions may change with the addition of optional accessories. Murdock Mfg. ™, Member of Morris Group
SELI M.	Signature (Approval for Manufacturing)		International [™] . Please visit www.murdockmfg.com for most current specifications.
MIIDE		5125 Proctor Avanua , City of Industry, CA 01746 USA	Q

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com